

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
8 July 2004 (08.07.2004)

PCT

(10) International Publication Number
WO 2004/057292 A1

(51) International Patent Classification⁷: G01L 17/00,
G01M 17/02, B60C 23/00

I-22060 Carimate (IT). MATRASCIA, Giuseppe [IT/IT];
Via Valassina, 14, I-20038 Seregno (IT).

(21) International Application Number:
PCT/IT2002/000815

(74) Agents: CASTIGLIA, Paolo et al.; Porta, Checcacci &
Associati S.p.A., Via Trebbia, 20, I-20135 Milano (IT).

(22) International Filing Date:
20 December 2002 (20.12.2002)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VC, VN, YU, ZA, ZM, ZW.

(25) Filing Language: Italian

(26) Publication Language: English

(71) Applicant (*for all designated States except US*): PIRELLI
PNEUMATICI S.p.A. [IT/IT]; Viale Sarca, 222, I-20126
Milano (IT).


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, SI, SK,
TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ,
GW, ML, MR, NE, SN, TD, TG).

(72) Inventors; and


(75) Inventors/Applicants (*for US only*): MONGUZZI, Carlo
[IT/IT]; Via Asiago, 9/E, I-20052 Monza (IT). ROSSI,
Franco [IT/IT]; Via Vasari, 9/F, I-20092 Cinisello Bal-
samo (IT). BRIVIO, Paolo [IT/IT]; Via del Ronco, 40,

[Continued on next page]

(54) Title: PROPERTIES OF A TIRE WITH SENSOR SIGNALS OF SPEED OF DEFORMATION



(57) Abstract: A method for measuring characteristic properties of a pneumatic tyre (2) for vehicle wheels comprises the steps of arranging at least one array of sensors (10) along a direction y transversal to a motion direction x of the tyre (2), making the tyre (2) pass at speed over least one array of sensors (10) along said direction x, detecting the speed of deformation of each sensor (10), generating, for each sensor (10), an electrical signal proportional to said speed of deformation and determining, starting from each detected electrical signal, at least one characteristic property of the tyre (2), for example the size and/or shape of the footprint area of the tyre (2). By integrating in time the electrical signal it is then possible to determine the distribution of pressure on such a footprint area. The sensors (10) comprise piezoelectric elements which, being known for having high frequency response, allow detection in high-speed conditions.



BEST AVAILABLE COPY

WO 2004/057292 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.